

Ely product codes

								Codes	Example
Model									
Ely A								EA	EB
Ely B								EB	
Ely B DS (2700K and 3000K Performance LED only)								EBDS	
								Ely C	EC
Mounting									
Pendant Easyfit™								E	E
Pendant Threaded								T	
U bracket square								UBS	
U bracket tear drop								UBT	
Light Engine									
Performance LED									32
8 LED								8	
16 LED								16	
24 LED								24	
32 LED								32	
48 LED								48	
64 LED								64	
Performance CoB									
Single CoB								PC	
Comfort CoB								CC	
Colour Temperature									
2700K								27	30
3000K								30	
4000K								40	
Distribution									
Roads - Diamond+ A Optic								A1 / A2 / A3 / A5 / A6	A1
Pathways - Diamond+ B Optic								B1 / B2 / B3	
Areas - Diamond+ C Optic								C1 / C2 / C6	
Crossings - Diamond+ Z Optic								ZR / ZL / ZF	
Wide Roads - AC1								AC1	
Pathways BC1								BC1	
Areas - CC1								CC1	
Roads - DC1								DC1	
Symmetric								SY	
Drive Current									
<p>Drive currents from 250mA to 1050mA are available in 50mA increments Insert drive current value (eg 750mA = 750)</p> <p>Notes Ely A 48/64 LED = 800mA maximum Ely A 32 LED = 900mA maximum Ely B 24/32 LED = 900mA maximum</p>								250 / 300 / 350 / 400 / 450 / 500 / 550 / 600 / 650 / 700 / 750 / 800 / 850 / 900 / 950 / 1000 / 1050	700
Product Colours									
RAL 9005 Black								10	10
RAL 7016 Anthracite grey								20	
RAL 7037 Dusty grey								21	
RAL 5003 Sapphire blue								30	
RAL 6005 Light moss green								50	
RAL 3005 Wine red								70	
Control									
No photocell								N	U
Miniature Photocell 35 lux (1:0.5)								U	
Part night switching Miniature Photocell 35 lux (1:0.5) (switch off midnight - 05:30) (Elexon regime 762)								A4	
Miniature Photocell 35 lux (1:0.5) + pre-programmed dimming (dimmed to 50% midnight - 05:30) (Elexon regime 531)								D8	
Integral CMS - Urban Control (Ely A & B only)								IUC	
Integral CMS - Telensa (Ely A & B only)								ITE	
Integral CMS - Mayflower (Ely A & B only)								IMA	
Pre-programmed dimming D4/SR Ready									
Example code = EB E 32 30 A1 700 10 U									

For further help specifying a product, please [contact us](#)