

Model	Colour Temperature (select)	Number of LEDs		Drive Current (mA)																	Average Efficacy (lm/W)		
				250	300	350	400	450	500	550	600	650	700	750	800	850	900	950	1000	1050			
160	4000K	6	lm	-	578	-	-	-	-	918	-	-	-	1218	-	-	-	-	-	-	-	93	
			W	-	5	-	-	-	-	11	-	-	-	15	-	-	-	-	-	-	-		
			lm/W	-	116	-	-	-	-	83	-	-	-	81	-	-	-	-	-	-	-		-
200		4000K	8	lm	-	1003	-	-	-	-	1592	-	-	-	2111	-	-	-	-	-	-	-	108
				W	-	9	-	-	-	-	15	-	-	-	20	-	-	-	-	-	-	-	
				lm/W	-	111	-	-	-	-	106	-	-	-	106	-	-	-	-	-	-	-	
Average Efficacy (lm/W)				-	114	-	-	-	-	95	-	-	-	93	-	-	-	-	-	-	-	-	

3000K and 2700K lumen outputs are calculated by applying an LOR to published 4000K data.
Check values against photometry file for actual lumen output.

Symmetric optic data.

Maximum Efficacy (lm/W)	116
-------------------------	-----

Light Output Reduction Factors	4000K	1.00
	3000K	0.91
	2700K	0.80