

Kirium Pro S4 product codes

	Code	Example
Construction		
Model		
Kirium Pro S4	KPS4	KPS4
Material		
Aluminium body with aluminium lower cover	A	A
Mounting		
Universal entry preset for direct post	A	A
Universal entry preset for side entry	B	
Colour		
RAL 7046 Mid grey	CF	CF
RAL 7035 Light grey	29	
RAL 9005 Black	10	
Other RAL colour (on request)	RAL [specify]	
Paint Type		
Polyester powder coat	PP	PP
Marine-grade coating	MG	
Light Source		
Light Engine		
168 LED	168	168
Colour Temperature		
3000K	30	30
4000K	40	
Distribution		
Roads - A Optic	A1 / A2 / A3 / A5 / A6	A1
Pathways - B Optic	B1 / B2 / B3	
Areas - C Optic	C1 / C2 / C6	
Drive Current		
Drive currents from 250mA to 650mA are available in 10mA increments. Insert drive current value (eg. 500mA = 500).		500
Control		
Control & Connectivity		
No control of connectivity	N	U20
Miniature photocell - 20 lux (1:1)	U20	
Miniature photocell - 20 lux (1:1) [top] + Zhaga socket [bottom]	U20Z	
Miniature photocell - 35 lux (1:0.5)	U35	
Miniature photocell - 35 lux (1:0.5) [top] + Zhaga socket [bottom]	U35Z	
NEMA socket - 6 pin / 7 pin [top]	B1 / D2	
NEMA socket - 7 pin [top] + Zhaga socket [bottom]	D2Z	
Zhaga socket - top / bottom / both	Z4 / Z4A / Z4B	
Optional Extras		
Tamper-proof screws	TP	-
Example Code - KPS4 A A CF PP 168 30 A1 500 U20		