

Kirium Wall product codes

	Codes	Example
Family		
Kirium	KIW	KIW
Light Engine		
8 LED	8	16
16 LED	16	
Drive Current		
300mA	300	300
500mA	500	
700mA	700	
Colour Temperature		
2700K	27	27
3000K	30	
4000K	40	
Distribution		
Narrow - Diamond+ A1 Optic	A1	A1
Medium - Diamond+ A5 Optic	A5	
Wide - Diamond+ C2 Optic	C2	
Glazing		
Clear	C	F
Frosted	F	
Product Colours		
RAL 9006 Aluminium	26	DB
RAL 9007 Metallic grey	27	
DB 703 Metallic dark grey	DB	
Corten brown	OB	
Mounting		
Standard wall mounting (no BESA conduit)	NB	NB
For mounting over horizontal BESA conduit box	B	
Control		
No photocell	N	IUC
Photocell 35 lux (1:0.5)	U	
Part night switching Photocell 35 lux (1:0.5) (switch off midnight - 05:30) (Elexon regime 762)	A4	
Photocell 35 lux (1:0.5) + pre-programmed dimming (dimmed to 50% midnight - 05:30) (Elexon regime 531)	D8	
Integral CMS - Urban Control	IUC	
Integral CMS - Telensa	ITE	
Integral CMS - Mayflower	IMA	
Presence Detector (optional)		
Presence detector	PD	-
Emergency Version (optional)		
3-hour emergency	EM	-
Example code = KIW 16 300 27 A1 F DB NB IUC		

For further help with specifying a product, please [contact us](#)