

Sephora product codes

				Codes	Example
Family					
Sephora				SEP	SEP
Style					
Radius				RA	RA
Cubis				CU	
Size					
450				45	HA
650				65	
		Halo		HA	
		Pendant Easyfit™		PEN	
Mounting					
Ø42 Side entry	Ø42 Side entry	Ø42 Side entry		42SE	CDPI
Ø76 Direct post	Ø76 Direct post	Ø76 Direct post		76DP	
Ø76 Post top				76PT	
	Ø114 Post top			11PT	
		Curved direct post (internal)		CDPI	
		Curved direct post (external)		CDPE	
			S1 bracket (see brochure)	S1	
			S2 bracket (see brochure)	S2	
			S3 bracket (see brochure)	S3	
			S4 bracket (see brochure)	S4	
			S5 bracket (see brochure)	S5	
Light Engine					
Performance				PE	PE
Colour Temperature					
2700K				27	27
3000K				30	
4000K				40	
Distribution					
Wide road - Diamond+ A Optic (A1)				A1	C3
Footpath - Diamond+ B Optic (B1)				B1	
Area - Diamond+ C Optic (C2 / C3)				C2 / C3	
Standard road - Diamond+ D Optic (D1)				D1	
Drive Current					
<p>The Performance engine is constant current and can be run at drive currents from 200mA to 800mA are available in 50mA increments. Insert drive current in 3-digit format (e.g. 700mA = 700)</p>					700
Product Colours					
RAL 9016 White				40	DB
RAL 9005 Black				10	
RAL 7035 Light grey				29	
RAL 7046 Mid grey				CF	
RAL 9006 Aluminium				26	
RAL 9007 Metallic grey				27	
DB 703 Metallic dark grey				DB	
Corten brown				CB	
Control					
No photocell				N	A4
Photocell 35 lux (1:0.5)				U	
Part night switching Photocell 35 lux (1:0.5) (switch off midnight - 05:30) (Elexon regime 762)				A4	
Photocell 35 lux (1:0.5) + pre-programmed dimming (dimmed to 50% midnight - 05:30) (Elexon regime 531)				D8	
3 pin NEMA (not compatible with Halo version)				E	
5 pin NEMA (not compatible with Halo version)				C3	
7 pin NEMA (not compatible with Halo version)				D2	
Example code = SEP RA HA CDPI PE 27 C3 700 DB A4					

For further help with specifying a product, please [contact us](#)