

Strand product codes

										Codes	Example
<b>Model</b>											
Strand A Plus										SAP	SA
Strand A										SA	
		Strand B								SB	
		Strand B DS (2700K and 3000K Performance LED only)								SBDS	
										Strand C	SC
<b>Mounting</b>											
Pendant Easyfit™										E	E
Pendant Easyfit™										T	
Pendant Threaded										UBS	
Pendant Threaded										UBT	
U bracket square											
U bracket tear drop											
<b>Light Engine</b>											
Performance LED											64
Performance LED										8	
Performance LED										16	
Performance LED										24	
Performance LED										32	
Performance LED										48	
Performance LED										64	
Performance LED										96	
Performance CoB											
Single CoB										PC	
Comfort CoB											
Single CoB										CC	
<b>Colour Temperature</b>											
2700K										27	30
3000K										30	
4000K										40	
<b>Distribution</b>											
Roads - Diamond+ A Optic										A1 / A2 / A3 / A5 / A6	A1
Pathways - Diamond+ B Optic										B1 / B2 / B3	
Areas - Diamond+ C Optic										C1 / C2 / C6	
Crossings - Diamond+ Z Optic										ZR / ZL / ZF	
Wide Roads - AC1										AC1	
Pathways BC1										BC1	
Areas - CC1										CC1	
Roads - DC1										DC1	
Symmetric										SY	
<b>Drive Current</b>											
<p>Drive currents from 250mA to 1000mA are available in 50mA increments            Insert drive current value (eg 750mA = 750)</p> <p><b>Notes</b>            Strand A Plus = 700mA maximum            Strand A = 900mA maximum</p>										250 / 300 / 350 / 400 / 450 / 500 / 550 / 600 / 650 / 700 / 750 / 800 / 850 / 900 / 950 / 1000 / 1050	700
<b>Product Colours</b>											
RAL 9005 Black										10	10
RAL 7016 Anthracite grey										20	
RAL 7037 Dusty grey										21	
RAL 5003 Sapphire blue										30	
RAL 6005 Light moss green										50	
RAL 3005 Wine red										70	
<b>Control</b>											
No photocell										N	A4
Miniature Photocell 35 lux (1:0.5)										U	
Part night switching Miniature Photocell 35 lux (1:0.5) (switch off midnight - 05:30) (Elexon regime 762)										A4	
Miniature Photocell 35 lux (1:0.5) + pre-programmed dimming (dimmed to 50% midnight - 05:30) (Elexon regime 531)										D8	
Integral CMS - Urban Control (Strand A Plus, A & B only)										IUC	
Integral CMS - Telensa (Strand A Plus, A & B only)										ITE	
Integral CMS - Mayflower (Strand A Plus, A & B only)										IMA	
Pre-programmed dimming											
D4i/SR Ready											
Example code = SA E 64 30 A1 700 10 A4											

For further help specifying a product, please [contact us](mailto:info@dw-windsor.com)